

## BRH-6522 Series

### Large Zoom Lens Housing



#### Features

- Accommodates large zoom lenses
- Powder Coated Aluminum
- All Stainless Steel Fasteners
- Heater and Sunshield Standard
- 24VAC and 115VAC Versions
- Designed to Meet IP67
- Cable Gland Fittings for Power, Data, Video

The BRH Series Camera Housings accommodate HD security cameras paired with large motorized zoom lenses to provide an ideal enclosure for outdoor installations in either hot or cold environments.

These models are constructed of durable powder coated aluminum and stainless steel fasteners to withstand harsh environments. Each unit is equipped with a heater, thermostat and sunshield. Video port is made from strengthened optically clear glass for HD video quality performance.

Cable connections are made at the rear of the housing using compression gland fittings for power, video, and lens connection cables.

BRH Series housings maintain a dry constant temperature inside the housing to maximize the operational lifetime of the equipment. The ample interior of usable space provides for onboarding accessories to improve the video performance.

#### Models:

BRH-6522-24G	Camera Housing, 24 VAC, Heater, Sunshield, Mount Plate, Cable Gland Connections
BRH-6522-12G	Camera Housing, 115/230-VAC, Heater, Sunshield, Mount Plate, Cable Gland Connections

#### Specifications:

IP Rating	Designed to meet IP67
Input Voltage	-24: 24VAC $\pm$ 10% -12: 100-240VAC
Heater Output	45W Max.
Heater Turn On/Off	67 $\pm$ 9 / 85 $\pm$ 5°F (19 $\pm$ 5 / 29 $\pm$ 3°C)
Field Connections	16-pin MS Connector
Viewing Window	Strengthened Glass
Operating Temp	-40 ~ 122°F (-40 ~ +50°C)
Construction	Powder Coated Aluminum, Glass View Window, Stainless Fasteners
Dimensions (in)	28" x 7.6" x 8.0" (L x W x H)
Dimensions (mm)	711 x 193 x 203mm (L x W x H)
Weight	16lbs (7.3kg)
Shipping Weight	19lbs (8.6kg)

